



Philadelphia Hardware Group, Inc.

6590 Top Gun Street
San Diego, CA 92121
www.philhardware.com

Tel
858.642.0450
858.545.2309
Fax
858.642.0454

AM Series

**Grade 3 Hollywood
Contemporary Style**

FEATURES

- Protection Sleeve Design
- Concealed Mounting Screws
- Panic Proof (inside always free)



ADA
Compliant



501AM-HW-US15

SPECIFICATIONS

Door Prep	Cross bore: 2-1/8" Edge bore: Edge Bore: 1" Latch Face: 1" x 2-1/4"
Backset	Fits both 2-3/8" and 2-3/4".
Door Fitting	1-3/8" ~ 2" door thick.
Exposed Trim	Zinc or Stainless steel. Lever is zinc alloy.
Latch	2-3/8" and 2-3/4" adjustable (9079). Bolt: 1/2" throw. Faceplate: 1" x 2-1/4" round corner.
Strike	Full lip 1-3/4" x 2-1/4" round corner (9103).
Door Handing	Universal, non-handing
Function	501AM – Passage 502AM – Privacy 515AM – Single Dummy
Finish	Factory available with US3, US10B, US15, US26, US26D, US12P Non stock item with minimum order quantity and longer delivery lead-time.
Lever Style	Hollywood (HW) Standard Other lever style may available with minimum order quantity and longer delivery lead-time.

SAN DIEGO

CHICAGO

SEATTLE