



6590 Top Gun Street
 San Diego, CA 92121
www.philhardware.com

Philadelphia Hardware Group, Inc.

Tel
 858.642.0450
 858.545.2309
 Fax
 858.642.0454

Category Bath Safety
Product Name Stainless Steel Grab Bar, Exposed Flange

		MATERIALS:	1 1/2" O.D. and 1 1/4" O.D. tubing is of .049 (18 gauge) type 304 stainless steel. Wall Flanges are of .125 (11 gauge) type 304 stainless steel. Flanges are heli-arc welded to tubing.																					
		FINISH:	Satin Stainless Steel																					
<table border="1"> <thead> <tr> <th>Item Code</th> <th>Dia. "A"</th> </tr> </thead> <tbody> <tr> <td>5121 "Size"</td> <td>1-1/2"</td> </tr> <tr> <td>5131 "Size"</td> <td>1-1/4"</td> </tr> </tbody> </table>		Item Code	Dia. "A"	5121 "Size"	1-1/2"	5131 "Size"	1-1/4"	SCREWS:	6pcs #10 x 2" Philip-head stainless steel screws															
		Item Code	Dia. "A"																					
5121 "Size"	1-1/2"																							
5131 "Size"	1-1/4"																							
<table border="1"> <thead> <tr> <th>Item Code</th> <th>18"</th> <th>24"</th> <th>30"</th> <th>36"</th> <th>42"</th> <th>48"</th> </tr> </thead> <tbody> <tr> <td>1-1/2"</td> <td>512018</td> <td>512024</td> <td>512030</td> <td>512036</td> <td>512042</td> <td>512048</td> </tr> <tr> <td>1-1/4"</td> <td>513018</td> <td>513024</td> <td>513030</td> <td>513036</td> <td>513042</td> <td>513048</td> </tr> </tbody> </table>		Item Code	18"	24"	30"	36"	42"	48"	1-1/2"	512018	512024	512030	512036	512042	512048	1-1/4"	513018	513024	513030	513036	513042	513048	MOUNTING:	Exposed Flange with 3 mounting holes on each end flange.
		Item Code	18"	24"	30"	36"	42"	48"																
1-1/2"	512018	512024	512030	512036	512042	512048																		
1-1/4"	513018	513024	513030	513036	513042	513048																		
		WALL CLEARANCE:	1-1/2"																					
		DESIGN:	Design to meet 1000 lb. pull when properly installed. Meet ADA, ANSI(A117.1-2003), and Federal Specifications.																					
		MEET ADA:	<ul style="list-style-type: none"> A. Tube: The diameter or width of the gripping surfaces of a handrail or grab bar shall be 1-1/4 in to 1-1/2 in (32 mm to 38 mm). B. Wall Clearance: If handrails or grab bars are mounted adjacent to a wall, the space between the wall and the grab bar shall be 1-1/2 in (38 mm) C. Structural Strength: able to support 250lbs including Tensile force. 																					



Philadelphia Hardware Group, Inc.

6590 Top Gun Street
 San Diego, CA 92121
www.philihardware.com

Tel
 858.642.0450
 858.545.2309
 Fax
 858.642.0454

Category Bath Safety
Product Name Stainless Steel Grab Bar, Concealed Flange

Item Code	Dia. "A"
5121 "Size"	1-1/2"
5131 "Size"	1-1/4"

Item Code	18"	24"	30"	36"	42"	48"
1-1/2"	512118	512124	512130	512136	512142	512148
1-1/4"	513118	513124	513130	513136	513142	513148

MATERIALS: 1 1/2" O.D. and 1 1/4" O.D. tubing is of .049 (18 gauge) type 304 stainless steel.
 Wall Flanges are of .075 (14 gauge) type 304 stainless steel. Flanges are heli-arc welded to tubing.

FINISH: Satin Stainless Steel

COVER: Snap in Type, .031 (22 gauge) type 304 stainless steel for two end flanges

SCREWS: 6pcs #10 x 2" Philip-head stainless steel screws

MOUNTING: 3 mounting holes on each end flange
 Concealed with Snap Flange cover

WALL CLEARANCE: 1-1/2"

DESIGN: Design to meet 1000 lb. pull when properly installed. Meet ADA, ANSI(A117.1-2003), and Federal Specifications.

MEET ADA:

- A. Tube: The diameter or width of the gripping surfaces of a handrail or grab bar shall be 1-1/4 in to 1-1/2 in (32 mm to 38 mm).
- B. Wall Clearance: If handrails or grab bars are mounted adjacent to a wall, the space between the wall and the grab bar shall be 1-1/2 in (38 mm)
- C. Structural Strength: able to support 250lbs including Tensile force.