

# 5000, 4400 SERIES

**ANSI GRADE 1**

**ANSI GRADE 1**

**ANSI/BHMA A156.4**

Series 2000, PT1

Exceeds 1,500,000 cycles with Backcheck



**LISTED**

UL10C Positive Pressure Rated. Conforms to UBC 7-2 (1997). (Uniform Building Code Standard)



**4400 Series**  
Comply with ANSI A117.1

**25-Year Warranty**

**Model**

- 5000** Adjustable power size 3-6 with Back Check
- 4400** Adjustable power size 1-4 with Back Check

**Applications**

- Heavy Duty Commercial model, ideal for high traffic door
- Versatile for new constructions, such as schools, hospitals, and public institutions
- Universal mounting hole pattern
- Size 4: CTC 9-1/16" x 3/4"
- Tri-packed for all type applications
- Sex-bolts included for Metal Door mounting



**Features**

- Multi-size spring adjustable power size 3-6, factory preset size 4
- Multi-size spring adjustable power size 1-4, factory preset size 3
- 4400 meets ADA, Barrier Free interior
- Standard with adjustable Backcheck

Product Specification	
Material	Aluminum alloy body, forged steel arm Heat treated forged steel piston Double Heat treated Steel pinion
Cover	Full plastic cover – standard
Valves	Triple valve control for Closing speed, Latching speed, and Back-check Staked valve for power adjustment
Arm & Brackets	Standard arm and parallel bracket included for different mounting demand
Screws	Self-tapping wood screws, machine screws, and sex-bolts
Finishes	Aluminum, Duronotic, and Gold

**Optional Functions**

- Hold Open Arm (4001)
- Drop Plate (see Accessories)

Technical Dimensions	
Series 5000, 4400	Size
A. Length of Closer Body	9-3/4" 9-3/4"
B. Horizontal Mounting Holes	9-1/16" 9-1/16"
C. Vertical Mounting Holes	3/4" 3/4"
D. Height of Closer Body	1-3/4" 1-3/4"
E. Projection from Door	2-7/8" 2-7/8"

End View

Front View

**Accessories**

**4001**  
**Hold-open Arm**  
Stand for pull side and top jamb  
Use with PA bracket for parallel arm mount



**HFW01**  
**Flat Wrench**  
For Hold Open Arm



**PAB02**  
**Parallel Bracket**  
for Hold Open Arm mounting can also use for regular parallel arm application



**40C**  
**Standard Full Plastic Cover**



**1348**  
**Sex-bolt with screw**  
For 1-3/4" standard Door Thick



**BSS02**  
**Blade Stop Spacer**  
Design to lower parallel arm shoe to clear 1/2" (13 mm) blade stop



**40DP-TJ**  
Size: 9-3/4" x 2-9/16"  
**Drop Plate –Top Jamb low ceiling clearance**  
For use when ceiling clearance is between 1-3/4" and 2-5/8"  
Cross reference: NORTON #1687



**40DP-PA**  
Size: 9-3/4" x 3-1/2"  
**Drop Plate –Parallel arm mount**  
Used to mount a closer on a top rail as narrow as 2-5/8" in height

